

LA CORPORATION DE VALVES



**TRUeline F8112 (ROUND PORT)**  
**FLOW COEFFICIENTS (C<sub>v</sub>)% OPEN**

VALVE SIZE	PERCENTAGE OPEN									
	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
2"	23	46	65	85	100	120	135	145	155	165
3"	70	142	200	255	310	360	405	440	475	500
4"	120	235	340	435	525	610	690	755	800	850
6"	285	565	810	1,025	1,250	1,460	1,635	1,795	1,920	2,020
8"	505	1,015	1,440	1,835	2,240	2,600	2,920	3,215	3,430	3,610
10"	810	1,615	2,310	2,950	3,590	4,160	4,680	5,140	5,490	5,780
12"	1,290	2,565	3,670	4,675	5,690	6,610	7,430	8,175	8,720	9,180
14"	1,485	2,965	4,240	5,410	6,570	7,630	8,565	9,410	10,090	10,600
16"	2,140	4,275	6,120	7,800	9,460	11,035	12,425	13,630	14,560	15,300
18"	2,805	5,600	8,000	10,185	12,430	14,390	16,170	17,760	18,970	20,000
20"	2,640	7,260	10,370	13,250	16,030	18,620	21,020	23,040	24,670	26,000
24"	5,390	10,760	15,420	19,590	23,860	27,700	31,320	32,240	36,570	38,200
30"	8,330	16,700	23,800	30,300	36,800	42,800	48,190	52,900	56,500	59,680
36"	12,550	25,110	35,930	45,780	55,700	64,700	72,700	79,980	85,390	89,900