



**TRUeline F8112 METAL SEATED VEE-ORIFICE
FLOW COEFFICIENTS (C_v)% OPEN**

VALVE SIZE	PERCENTAGE OPEN									
	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
2"	1.3	4	9	14	22	32	40	50	58	64
3"	3.7	12	24	42	65	91	116	145	168	185
4"	7.2	23	47	83	126	177	228	282	329	362
6"	16	53	107	186	283	401	515	636	739	815
8"	32	105	203	356	539	765	981	1,209	1,416	1,555
10"	50	164	329	582	886	1,244	1,593	1,975	2,302	2,531
12"	75	243	487	861	1,312	1,835	2,360	2,918	3,411	3,744
14"	101	319	651	1,160	1,753	2,449	3,151	3,908	4,549	5,000
16"	133	422	868	1,546	2,336	3,259	4,196	5,200	6,068	6,657
18"	161	538	1,048	1,858	2,821	3,951	5,085	6,285	7,338	8,055
20"	201	661	1,298	2,295	3,501	4,898	6,291	7,798	9,091	9,989
24"	294	989	1,932	3,408	5,191	7,261	9,330	11,576	13,441	14,811

**TRUeline F8112-VP METAL SEATED VEE-ORIFICE
FLOW CHARACTERISTIC CURVE**

